

IDEAS become REALITY



INNOVATIVE TECHNOLOGY - MADE IN GERMANY

The Unidirectional Tape

The aim of lightweight construction is to reduce weight, save raw materials, reduce costs and energy consumption in the production. The **proUD-Tapes** powered by Profol fulfill these goals. proUD is fully recyclable and reduces the CO₂ footprint by factor 4 compared to aluminum. **proUD-0°** guaranties the maximum in unidirectional strength.

proUD-0° Glass-PP 0° UD-tape rolls up to 800 mm diameter. Slass-PP 90° UD-tape tape rolls up to 800 mm diameter. Slass-PP 90° UD-tape tape rolls up to 800 mm diameter. Slass-PP 90° UD-tape tape rolls up to 800 mm diameter. Slass-PP 90° UD-tape tape rolls up to 800 mm diameter. Slass-PP 90° UD-tape tape rolls up to 800 mm diameter.

Specifications

- · 66% 72% continuous glass fibre
- · 28 % 34 % polypropylene
- · Density 1.65 g/cm³
- · Weight 330 g/m²

- · Tape thickness 200 µm
- · Width 1 250 mm
- · On roll
- \cdot Length up to 2 200 m



Contact:

Lars Wilkening | +49 172 6061819 | lwilkening@profol.de Oliver Rüsseler | +49 171 2423512 | oruesseler@profol.de

www.profol.com/progano

